



## PP compression fittings

# Coude 90° taraudé, renforcé

## ITEM 483

RÉFÉRENCE	DESCRIPTION	Poids net	Volume (m <sup>3</sup> )	Poids brut	Unités par lot
112E129	90° ELBOW, FEMALE THREAD REINF 20X1/2"	0,065541	0,02243	5,731	80
112E130	90° ELBOW, FEMALE THREAD REINF 25X3/4"	0,094838	0,03129	8,16	80
112E131	90° ELBOW, FEMALE THREAD REINF 32x1"	0,132763	0,04117	9,27	65
112E132	90° ELBOW, FEMALE THREAD REINF 40 x 1 1/4"	0,235	0,03682	10,02	40
112E133	90° ELBOW, FEMALE THREAD REINF 50 x 1 1/2"	0,348	0,06347	14,68	40
112E134	90° ELBOW, FEMALE THREAD REINF 63 x 2"	0,596	0,06347	15,204	24
112E135	90° ELBOW, FEMALE THREAD REINF 75 x 2 1/2"	0,992	0,04460	10,75	10
112E136	90° ELBOW, FEMALE THREAD REINF 90 x 3"	1,74	0,03129	9,26	5
112E137	90° ELBOW, FEMALE THREAD REINF 110 x 4"	2,423	0,02244	5,386	2
112E384	90° ELBOW, FEMALE THREAD REINF 32x3/4"	0	0,03129	0	65





## ITEM 483 | Coude 90° taraudé, reforcé

Código	f tubo - F	Peso (g)	A	B	C	D	E	PN	TIPO ROSCA
12E129	20 - 1/2"	64	21	46	87	57	20	PN16	BSP
12E130	25 - 3/4"	89	26	55	97	65	20	PN16	BSP
12E384	32 - 3/4"	132	33	64	111	76	20	PN16	BSP
12E131	32 - 1"	128	33	64	111	76	22	PN16	BSP
12E132	40 - 1 1/4"	235	42	76	138	91	25	PN16	BSP
12E133	50 - 1 1/2"	348	51	91	153	106	25	PN16	BSP
12E134	63 - 2"	596	64	109	189	120	29	PN16	BSP
12E135	75 - 2 1/2"	992	77	133	220	142	34	PN10	BSP
12E136	90 - 3"	1740	92	159	267	165	42	PN10	BSP
12E137	110 - 4"	2423	112	183	303	201	51	PN10	BSP





## ITEM 483 | Coude 90° taraudé, renforcé

---



Pol. Ind. Plá Vallonga,  
c/ Agua, 28  
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Service d'Attention  
Technique Commerciale  
+34 966 105 888



[www.hidroten.es](http://www.hidroten.es)



## Documentation Produit



## Certifications de produits

## Certificats d'entreprise

