



Vannes à boisseau 'Basic'

Sortie taraudée - FPM - Système Basic ITEM 223



| RÉFÉRENCE | DESCRIPTION | Poids net | Volume (m ³) | Poids brut | Unités par lot |
|-----------|------------------------------|-----------|--------------------------|------------|----------------|
| 1011272 | VALV.ENLACE S/H VITON 4" | 5,84 | 0,04460 | 12,52 | 2 |
| 1011492 | VALV.ENLACE S/H VITON 1/2" | 0,154 | 0,02244 | 7,201 | 40 |
| 1011493 | VALV.ENLACE S/H VITON 3/4" | 0,211183 | 0,02244 | 8,935 | 40 |
| 1011494 | VALV.ENLACE S/H VITON 1" | 0,366067 | 0,03129 | 11,555 | 30 |
| 1011495 | VALV.ENLACE S/H VITON 1 1/4" | 0,62585 | 0,03129 | 13,09 | 20 |
| 1011496 | VALV.ENLACE S/H VITON 1 1/2" | 0,8998 | 0,03129 | 14,07 | 15 |
| 1011497 | VALV.ENLACE S/H VITON 2" | 1,42708 | 0,03682 | 14,82 | 10 |
| 1011498 | VALV.ENLACE S/H VITON 2 1/2" | 2,8017 | 0,03129 | 11,78 | 4 |
| 1011499 | VALV.ENLACE S/H VITON 3" | 4,4062 | 0,02244 | 9,3 | 2 |





ITEM 223 | Sortie taraudée - FPM - Système Basic

| CÓDIGO | r | DN | PESO (g) | A | B | C | D | E | F | PN | TIPO ROSCA |
|--------|--------|-----|----------|-----|-----|----|-----|-----|-----|------|------------|
| 11492 | 1/2" | 15 | 154 | 91 | 52 | 17 | 78 | 94 | 47 | PN16 | BSP |
| 11493 | 3/4" | 20 | 211 | 101 | 59 | 20 | 84 | 100 | 51 | PN16 | BSP |
| 11494 | 1" | 25 | 366 | 120 | 70 | 23 | 97 | 140 | 66 | PN16 | BSP |
| 11495 | 1 1/4" | 32 | 626 | 134 | 84 | 26 | 128 | 161 | 72 | PN16 | BSP |
| 11496 | 1 1/2" | 40 | 899 | 153 | 99 | 33 | 142 | 171 | 77 | PN16 | BSP |
| 11497 | 2" | 50 | 1403 | 161 | 121 | 29 | 165 | 182 | 90 | PN16 | BSP |
| 11498 | 2 1/2" | 65 | 2746 | 204 | 151 | 33 | 222 | 275 | 121 | PN10 | BSP |
| 11499 | 3" | 80 | 4406 | 234 | 175 | 36 | 244 | 290 | 141 | PN10 | BSP |
| 11272 | 4" | 100 | 5840 | 267 | 210 | 42 | 307 | 426 | 155 | PN10 | BSP |





Documentation Produit



Certifications de produits

Certificats d'entreprise

